



## APC SmartUPS 3000VA

To Receive Detailed Quotation Call: 800-306-1125  
 or Complete Order Form And Fax To: 800-306-1126

Condition	Pre-Owned
Model	SmartUPS
Part Number	SU3000RMNET
Phase	Single Phase
KVA	3
Input Voltage	120V – L5-30P
Output Voltage	120V (8) 5-15R
Frequency (Hz)	60
Dimensions H x W x D	Inches 8.76" x 19" x 17.76"
Weight	129 lbs
Warranty	1 Year Warranty
Runtime Batteries	New Batteries Included/Installed
Price	\$ 520.00



Rackmount Kit Included  
 New Batteries Included

Data Sheet: [http://www.apc.com/resource/include/techspec\\_index.cfm?base\\_sku=SU3000RMNET](http://www.apc.com/resource/include/techspec_index.cfm?base_sku=SU3000RMNET)

<b>Bill to:</b> _____ Company Name _____ Contact Name _____ Address _____ City State Zip _____ Phone Fax _____	<b>Ship to:</b> _____ Company Name _____ Contact Name _____ Address _____ City State Zip _____ Phone Fax _____
--	--

BUY

SELL

LEASE

RENT

TRADE

## **Output**

Output Power Capacity  
2250 Watts / 3000 VA

Max Configurable Power  
2250 Watts / 3000 VA

Nominal Output Voltage  
120V

Output Voltage Distortion  
Less than 5% at full load

Output Frequency (sync to mains)  
47 - 53 Hz for 50 Hz nominal, 57 - 63 Hz for 60 Hz nominal

Crest Factor  
up to 5 : 1

Waveform Type  
Sine wave

Output Connections  
(8) NEMA 5-15R



## **Input**

Nominal Input Voltage  
120V

Input Frequency  
50/60 Hz +/- 3 Hz (auto sensing)

Input Connections  
NEMA L5-30P



Cord Length  
6 feet (1.83 meters)

Input voltage range for main operations  
92 - 147V

Input voltage adjustable range for mains operation  
86 - 154V

## **Batteries & Runtime**

Battery Type  
Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof

Typical recharge time  
3 hour(s)

Replacement Battery  
[RBC11](#)

RBC™ Quantity  
1

Typical Backup Time  
at Half Load  
19.2 minutes (1125 Watts)

Typical Backup Time  
at Full Load  
5.7 minutes (2250 Watts)

Runtime Chart

[Smart-UPS](#)

## ***Communications & Management***

Interface Port(s)

DB-9 RS-232, SmartSlot

Available SmartSlot™ Interface Quantity

1

Control panel

LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators

Audible Alarm

Alarm when on battery : distinctive low battery alarm : configurable delays

Emergency Power Off (EPO)

Optional

## ***Surge Protection and Filtering***

Surge energy rating

880 Joules

Filtering

Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## ***Physical***

Maximum Height

8.76 inches (222 mm)

Maximum Width

19.00 inches (483 mm)

Maximum Depth

17.76 inches (451 mm)

Rack Height

5U

Net Weight

129.00 lbs. (58.64 kg)

Shipping Weight

145.00 lbs. (65.90 kg)

Shipping Height

13.26 inches (337 mm)

Shipping Width

24.50 inches (622 mm)

Shipping Depth

24.00 inches (610 mm)

Color

Beige

Units per Pallet

6.00

## ***Environmental***

Operating Environment

32 - 104 °F (0 - 40 °C)

Operating Relative Humidity

0%

Operating Elevation

0-10000 feet (0-3000 meters)

Storage Temperature

5 - 113 °F (-15 - 45 °C)

Storage Relative Humidity

0%

Storage Elevation

0-50000 feet (0-15000 meters)

Audible noise at 1 meter from surface of unit

53.00 dBA

Online Thermal Dissipation

375.00 BTU/hr

## **Conformance**

Regulatory Approvals

CSA,FCC Part 15 Class A,UL 1778